BIVASCA RIBALTABILE POSTERIORE DA 3+2 MC

PIAGGIO PORTER













PIAGGIO PORTER

VRP 3+2

Bivasca ribaltabile posteriore da 3+2 mc

Dati tecnici		
Volume	m^3	3+2
M.T.T.	kg	2.800
Passo del veicolo	mm	3.000
Altezza	mm	2.200
Lunghezza max	mm	5.003
Larghezza max	mm	1.796
Tara veicolo allestito	kg	2.100
Portata utile	kg	700

Allestimento

L'ultimo nato in casa ECO SERVICE è stato progettato per soddisfare le continue richieste di un settore, quello dei rifiuti, sempre molto esigente ed in continua espansione. La geometria costruttiva con cui è realizzato, è stata studiata per facilitare la gestione polifunzionale delle due tipologie di rifiuto trasportabili. Rendendo il VRP 3+2 di facile abbinamento con gli impianti di compattazione satellite. A completare la già qualitativamente valida dotazione di serie, curata nei minimi particolari, vi è la possibilità di personalizzare ulteriormente gli allestimenti, seguendo le richieste imposte dal cliente e dagli ambiti lavorativi.

Accessori

- Vasche in lamiera di acciaio capacità 3mc + 2mc
- Alza volta contenitori con attacchi bidoni 120/240/360 litri per entrambe le vasche
- Piedi stabilizzatori idraulici
- Valvole di blocco di sicurezza su tutti i cilindri
- Angolo di ribaltamento vasche 85°
- Presa di forza con pompa da 16 l/min
- Segnalazioni luminose
- Funzioni macchina in cabina
- Puntone di sicurezza sotto vasca
- Avvisatore acustico manovre comandi attrezzatura con cavo estendibile
- Faro di lavoro notturno, lampeggiante colore arancio omologato,
- cassetta porta attrezzi, supporto calzatoia per ruota,
- Impianto elettrico/acustico a norma CE.

3+2 mc rear double waste tipping body

Technical sheet		
Volume	m^3	*3+2*
M.T.T.	kg	*2.800*
Wheelbase of the vehicle	mm	*3.000*
Height	mm	*2.200*
Max length	mm	*5.003*
Max width	mm	*1.796*
Outfitted vehicle tare weight	kg	*2.100*
Payload	kg	*700*

Outfitting

The latest addition to the ECO SERVICE range was designed to meet the ongoing standards of the waste management sector which is always very demanding and constantly expanding. The constructive geometry, which it is made with, has been studied to facilitate the multifunctional management of the two types of transportable waste. Making the VRP 3+2 easy to combine with satellite compaction systems. In order to complete the current qualitatively valid standard equipment paying attention to the smallest details, there is the possibility to customize the fittings according to customers requests and different working environments.

Accessories

- *Waste collection bodies in sheet steel capacity 3mc + 2mc*
- *Container lifter with 120/240/360 liter bin attachments for both bodies*
- *Hydraulic stabilizers,*
- *Safety shut-off valves on all cylinders*
- *85° body tilting angle*
- *Power with 16l/min pump*
- *Machine function light indicators in the cab*
- *Safety strut under the body*
- *Warning acoustic alarms*
- *Equipment controls with extensible cable*
- *Safety light*
- *Approved orange flashing lights*
- *Toolbox, wheel chock support,*
- *Electric/acoustic system in compliance with CE regulations*