VASCA RIBALTABILE
A COSTIPATORE DA 5,5 MC

PIAGGIO PORTER













PIAGGIO PORTER

VRP 5,5

Vasca ribaltabile a costipatore da 5,5 mc

Dati tecnici	
Alimentazione motore	Benzina/GPL - Benzina/Metano
Potenza motore	78 kW
Normativa	CEE Euro 6D
Assi	2
M.T.T.	Kg 2.800
Portata utile	Kg 600
Capacità Vasca	mc 5,5
P: Passo	mm 3.250
Lmax: Lunghezza massima	mm 5.298
Lv: Lunghezza vasca	mm 3.100
A: Sbalzo anteriore	mm 640
S: Sbalzo posteriore	mm 1.415
Hmax: Altezza veicolo	mm 2.200
Wmax: Larghezza max veicolo allestito	mm 1.700

Caratteristiche attrezzatura

- Vasca in lamiera di acciaio FE360 elettrosaldato della capacità di 5,5mc c.a. con struttura completamente elettrosaldata a filo continuo e a perfetta tenuta stagna con spessori lamiere laterali e fondo da 1,5 mm;
- Telaio in acciaio speciale ad alta resistenza in tubolare munito di traverse antitorsione;
- Sistema di scarico del rifiuto per ribaltamento posteriore angolo max 87°;
- Dispositivo voltacontenitori comprendente attacco a pettine per l'aggancio di bidoni da 120, 240, 360 litri anche in coppia e 1100 litri singolo. Il sistema è composto da due coppie di bielle azionate da due cilindri oleodinamici che consentono di effettuare una doppia rotazione a salita verticale per evitare la caduta di rifiuti a terra durante l'operazione di scarico;
- Dispositivo di costipazione a pala articolata che consente un rapporto di compattazione minimo di 8:1;
- Piedi stabilizzatori idraulici per garantire la stabilità del veicolo in fase di ribaltamento;
- Faro bianco per lavoro notturno;
- Faro rotante a luce arancio omologato;
- Cicalino acustico di segnalazione retromarcia;
- Cilindri oleodinamici muniti ciascuno di valvole di blocco.

5.5 mc tipping waste body with compactor

Technical sheet	
Fuel Type	*Petrol/LPG - Petrol/Natural Gas*
Engine power	*78 kW*
EU emissions standard	*CEE Euro 6D*
Axles	*2*
GVM	*Kg 2.800*
Payload	*Kg 600*
Body Capacity	*mc 5,5*
P: Wheelbase	*mm 3.250*
Lmax: Max length	*mm 5.298*
Lv: Body length	*mm 3.100*
A: Front overhang	*mm 640*
S: Rear overhang	*mm 1.415*
Hmax: Vehicle height	*mm 2.200*
Wmax: Converted vehicle max width	*mm 1.700*

Equipment characteristics

- *Arc welded FE360 steel body with approx. capacity of 5.5mc, sealed full bead welded structure and 1.5 mm gauge side walls and floor;*
- *Special high-strength tubular steel frame with cross brace reinforcements;*
- *Waste discharge system by rear tipping with max angle of 87°*
- *Container turning device including lift comb coupling for 120, 240, 360 litre bins, also in pairs, and 1100 litre single bin. The system is composed of two pairs of cranks operated by two hydraulic cylinders that allow vertical ascent with double rotation to prevent waste spills to ground during discharge;*
- *Hydraulic outriggers to stabilize vehicle during tipping;*
- *Spotlight for night-time operations;*
- *Type approved rotary orange beacon;*
- *Reversing beeper;*
- *Hydraulic cylinders, each equipped with load-holding valves*
- *Control to enable container overturning and discharge designed to eliminate hand-arm crushing risks, in compliance with statutory safety regulations;*
- *Wheel chocks holder;*
- *RH holder for brush and shovel;*
- *Rear lever operated controls for container lift-turn function.*